

LUBRICATION



ALTERNA Lubricant for compressors

DESCRIPTION

ALTERNA are premium ash-free lubricants for the lubrication of reciprocating and rotary air compressors and vacuum pumps.

ADVANTAGES

- High oxidation and good thermal stability
- Excellent hydrolytic stability
- Prevents sludge formation, good protection against corrosion
- Very low acid number
- Good demulsifying and foam behaviour

PROPERTIES

Characteristics	Specifications	ALTERNA 68	ALTERNA 100	ALTERNA 150
Specific Gravity (Kg/L at 20°C)	ASTM D4052	0.858	0.863	0.872
Viscosity at 40°C	ASTM D445	68	97	150
Viscosity at 100°C	ASTM D445	9.3	11.7	15.4
Viscosity Index	ASTM D2270	114	109	104
Flash point COC (°C)	ASTM D92	232	234	242
Pour point (°C)	ASTM D97	-38	-32	-26

FIELDS OF USE

ALTERNA meets the following standards:

- DIN 51506 – VBL, VCL, VDL
- ISO / DP 6521 (DAA, DAB, DAH, DAG)

The specifications of our products only become definitive at the time of order, which is subject to our general sale and guarantee conditions. The general characteristics of our products may change to provide our customers with the benefits of technical developments. The safety data sheet of this product is available on www.motul.com.

VILUBE member of MOTUL Asia Pacific
Tuilidonai Building 11th FI, 119 Dien Bien Phu St., Dist. 1, Hochiminh City
T (84 8) 3911 8601 - Ext: 333 * F (84 8) 3911 8602 * M (84) 908 642 442
www.motul.com

Creation date: 2013/12/12
Revision date: 2016/04/25