


LUBRICATION



SUPRACAL Heat Transfer Oil

DESCRIPTION

SUPRACAL is a high performance heat transfer fluid created from high refined base oils and advanced additive systems. This combination of materials provides superior performance in both closed and open heat transfer systems with forced circulation.

ADVANTAGES

- High oxidation and thermal stability
- Extremely low vapour pressure
- Contains additives to prevent deposits, which allows effective fluid filtration
- Excellent lubricating power
- Very High flash point for maximum system efficiency
- Coats all system surfaces with a protective fluid film

PROPERTIES

CHARACTERISTICS	SUPRACAL 32	SUPRACAL 105	UNIT	TEST METHODS
Appearance	Bright, clear	Bright, clear		
Kinematic Viscosity at 40°C	30.9	101.9	cSt	ASTM D445
Kinematic Viscosity at 100°C	5.3	12.1	cSt	ASTM D445
Viscosity Index	103	109	-	ASTM D2270
Density at 20°C	0.855	0.861	Kg/L	ASTM D4052
Flashpoint	226	252	°C	ASTM D92
Pour Point	-33	-33	°C	ASTM D97
Foaming, Seq I - II - III	0/0 - 10/0 - 0/0	0/0 - 10/0 - 0/0	ml/ml	ASTM D 892


SPECIFICATIONS

- ISO 6743/12 Class L Family Q: QB (SUPRACAL 32), QC (SUPRACAL 105)
- DIN 51502 Class L

VILUBE member of MOTUL Asia Pacific
 Tuilidonai Building 11th Fl, 119 Dien Bien Phu St., Dist. 1, Hochiminh City
 T (84 8) 3911 8601 - Ext: 333 * F (84 8) 3911 8602 * M (84) 908 642 442
www.motul.com

Creation date: 2012/12/13
 Revision date: 2013/10/04

LUBRICATION



SUPRACAL Heat Transfer Oil

FIELDS OF USE

SUPRACAL is used for heat transfer systems in the following industries

- Plastic and Rubber industry
- Paper Industry
- Cement Industry
- Textile industry (treatment, finishing)
- Chemical industry

The specifications of our products only become definitive at the time of order, which is subject to our general sale and guarantee conditions.

The general characteristics of our products may change to provide our customers with the benefits of technical developments. The safety data sheet of this product is available on www.motul.com.

VILUBE member of MOTUL Asia Pacific
Tuilidonai Building 11th Fl, 119 Dien Bien Phu St., Dist. 1, Hochiminh City
T (84 8) 3911 8601 - Ext: 333 * F (84 8) 3911 8602 * M (84) 908 642 442
www.motul.com

Creation date: 2012/12/13
Revision date: 2013/10/04