


LUBRICATION



IRIX LSM

DESCRIPTION

IRIX LSM are extreme-pressure greases formulated from premium mineral base oils and a Lithium thickener.

ADVANTAGES

- ➔ Excellent protection against corrosion
- ➔ Excellent extreme-pressure performance and wear protection
- ➔ Good water leaching resistance
- ➔ Very good adhesion
- ➔ Recommended for usage in central lubrication systems

TECHNICAL INFORMATION

| Characteristic | Standard | IRIX LSM | | | | |
|----------------------------|-------------|--------------|-------|-------|-------|-------|
| | | 1500 | 150 | 151 | 152 | 153 |
| Colour | | Amber | | | | |
| Base | | Mineral oil | | | | |
| Thickener | | Lithium | | | | |
| Base oil viscosity at 40°C | NF T 60 100 | 130 cSt | | | | |
| NLGI grade | DIN 51818 | 00 | 0 | 1 | 2 | 3 |
| Drop point | ISO 2176 | 175°C | 165°C | 150°C | 190°C | 190°C |
| Weld load, kg | ASTM D2596 | 315 | | | | |
| Operating temperature | ISO 11008 | -20 to + 130 | | | | |

FIELDS OF USE

The **IRIX LSM** grease is designed for the lubrication of bearings, slides, gears and all mechanical components operating under high loads.

IRIX LSM 1500 can also be used for machine-tools slideways, where a 00 grade grease is recommended.

The specifications of our products only become definitive at the time of order, which is subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available on www.motul.com

MOTUL - 119, Bd Félix Faure BP 94 - 93303 AUBERVILLIERS CEDEX
Tél : +33 1 48 11 70 30 Fax : +33 1 48 11 70 38
www.motul.com